

CUSTOMER FOCUSED. SOLUTION DRIVEN.



GEO 9/12 Grout Pump

- 49.5 HP Kubota diesel engine, Tier 4 Final
- 2 x 80 gal mixing tanks with paddle mixers
- Optional 60 gal/minute and up to 1800 psi



NOW DELIVERING TO U.S. MARKETS.
Contact Riley VanSchepen at 616.422.2397.

INTRIC
GROUTING SOLUTIONS

www.INTRICSOLUTIONS.com



INTRIC GEO 9/12 Grout Pump

STANDARD FEATURES

Frame

- Skid mounted steel frame, partially encased
- Forklift slots
- Powder coat

Two-Piece Mixing Tank

- Round tank with access door
- Tank capacity: 80 gallon (approx 300 l)
- Hopper with bag ripper

Tools in Mixing Tank

- Specially designed paddle and baffles to develop a smooth and consistent grout mixture.

Operating Elements

- Two turning knobs for variable speed mixing
- Turning knob for adjusting maximum pressure
- Turning knob for changing speed of delivery rate (l/min/U.S. gal/min)
- On/off switch for delivery pump (grouting pump)
- 2 x on/off button for semi-automatic water dosage (special equipment SA 7/2)

Water Dosage

- Water distributor with flushing connection
- Water-holding and dosing tank 2 x 60 gal
- Two-piece, hand-operated outlet valve

Delivery Pump

- Double-acting, single-piston, horizontal pump

Delivery Pressure

- Pressure transmitter to digital indicator

Hydraulic

- Oil tank capacity 40 gallon (approx. 151.42 l)
- Oil filling and breather filter
- Oil level and temperature indication
- Electric cooling fan

Diesel Drive

- Three-cylinder Kubota Diesel Engine, Tier 4 Final, liquid-cooled
- 49.5HP
- Tank capacity 22 gallon (approx 83.28 l)
- Starter battery

Optional Extras • Spare parts sets • Pressure hoses • Remote controls • Pressure washer

TECHNICAL DATA

Engine

Kubota Diesel Engine, Tier 4 Final, Stage III B
49.5HP. Fuel Burn Rate:

- 2200 rpm = 2.22 gal/h • 2400 rpm = 2.48 gal/h

Mixing Tank

- Adjustable mixing speed from 0-200 rpm hydraulic driven
- Capable of mixing a 0.45-1.0 BTU using silica sand and 0.45-1.20 using graphite
- Capacity: 2 x 80 gal

Grout Pump

- Single hydraulic-driven, double-acting piston pump, check valve operated suction and pressure valves
- Maximum Flow: 30 gal/min (113.5 liter/min)*
- Maximum Pressure: 1800 PSI (120 bar)*
- Optional 60 gal/min pump

Power Pack

- Power pack contains hydraulic tank (40 gal) and diesel tank (22 gal) as well as diesel engine and hydraulic intelligence

Digital Screen

- Monitor flow and pressure on internal digital screen. Volume is calculated by stroke counting.**

Specifications

- Dimensions: 47x95x75
- Weight: 3800 lbs

**Both maximum performances are not reachable at the same time.*

***Flow on display is a theoretical calculated volume by counting the strokes. Accuracy can be off by 100% (if suction line is not connected or hoses are plugged, etc., pump will continue to count!).*