


The Comacchio MC-E 30 is a robust drilling attachment designed for operation in restricted access and challenging environments, such as docks, road edges, rock walls, and slopes. It mounts on the end of hydraulic excavator booms, utilizing the excavator's movements and hydraulics to allow for a wide range of mast positions and inclinations. Engineered for flexibility, it enables efficient drilling for micropiles, anchors, and ground consolidation projects in confined or hard-to-reach areas.





Comacchio MC-E 30 Specifications

Technical Specifications

Parameter	Value
Excavator Class	18-20 ton
Weight	2,500-3,500 kg (5,500-7,700 lbs)
Mast Feed Stroke	3,500 mm (11.4 ft)
Feed Force	5,000 daN (11,240 lbs)
Retract Force	5,000 daN (11,240 lbs)
Rotary Torque	88–1,400 daNm (649–10,325 lb·ft)
Rotary Speed	43-380 rpm
Excavator Class	18-20 ton

Options & Accessories

- Rod carousel, adapters, & accessories
- Mountings for jet grouting, rotary drilling, percussion

Key Features

- For hydraulic excavators
- Works in limited-access and space
- Fully remote-controlled
- Patented mast joint support
- Compatible with multiple rotary heads

Transport Dimensions	
Parameter	Value
Transport Width	1,195 mm (3' 11")
Transport Height	1,420 mm (4' 8")
Transport Length	5,455 mm (17' 11")
Transport Weight	1,850 kg (4,090 lbs)

Sales and Service

National Piling Products, Inc. 1159 Electric Ave, Suite E Wayland, MI 49348 Tel: 1-855-801-7453 www.nppius.com

